

Your AP 5.4 / AP 5.6 at a glance

Printer specifications: AP 5.4		AP 5.6
Printing technology:	Thermal transfer/direct	Thermal transfer/direct
Size (H x W x D):	272 x 260 x 462	272 x 337 x 462
Weight:	14 kg	15.5 kg
Printhead:	203 or 300 dpi; printwidth: 104 / 105 mm	203 or 300 dpi; printwidth: 168 mm
Print speed:	50 - 200 mm/s / 50 - 150 mm/s	50 - 200 mm/s / 50 - 150 mm/s
Display:	2-line LCD, 16 characters	2-line LCD, 16 characters
Processor:	32 Bit RMI CPU	32 Bit RMI CPU
Memory:	4 MB Flash, 32 MB SDRAM	4 MB Flash, 32 MB SDRAM
Printable barcodes:	EAN 8, EAN 13 with add-on 2 and 5; UPC-A, UPC-E; Code 39; Code 39 extended; Code 39 Ratio 3:1; Code 39 Ratio 2,5:1; ITF, Codabar; Code 128 A, B, C; Code 128 UPS; Code 128 Pharmacy; Code 2/5 Matrix; Code 2/5 Interleaved; Code 2/5 5; Code 2/5 Interleaved Ratio 1:3; Code 2/5 Matrix Ratio 1:2,5; Code 2/5 Matrix Ratio 1:3; MSI; EAN 128; Postcode (Guide and Identity Code); All bar codes scalable in 16 widths and the height; 2-dimensional Data Matrix Code; Maxi Code; PDF 417; Codablock F; Code 49; QR Matrix Code; GS1 Databar; EAN/UCC composite symbology	
Standard fonts:	17 fonts including OCR-A and OCR-B; 3 scalable fonts, True Type fonts (also unicoded) supported	
Interfaces:	10/100 Base-T Ethernet; 2 x USB, RS232 Serial	10/100 Base-T Ethernet; 2 x USB, RS232 Serial
Font magnification:	TBC	TBC
Operating temperature:	5 - 40 °C; humidity: 30 - 85% non-condensing	5 - 40 °C; humidity: 30 - 85% non-condensing
Power supply:	100 - 240 V (AC); Mains frequency 60/50 Hz	100 - 240 V (AC); Mains frequency 60/50 Hz
Accessories/upgrade options:	Cutter; Internal rewinder; External rewinder; Dispenser light barrier; Keyboard	
Special features:	Reflex Sensor; WLAN (future option); Signal Interface (future option)	
Label width:	15 to 120 mm	50 to 185 mm
Label length:	5 to 8000 mm	5 to 8000 mm
Roll length:	210 m	210 m
Foil length:	450 m	450 m

Avery Dennison ist rund um
die Welt für Sie da:

Benelux
Dänemark / Skandinavien
Frankreich

Iberische Halbinsel
Indien

Italien
Polen
VR China/Hongkong

Türkei
VAE
USA

Avery Dennison Deutschland GmbH
Ohmstraße 3, D-85386 Eching
Tel.: +49/(0) 81 65/925 - 299
Fax: +49/(0) 81 65/6 43 60
info.deutschland@eu.averydennison.com
www.monarch.averydennison.com

